

Product datasheet

Specifications



APC Back-UPS 1100VA, 230V, without auto shutdown software, 5 India outlets (1 surge)

BX1100C-IN

Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Rated power in W	660 W
Rated power in VA	1100 VA
Nb of power socket outlets	4 India 2/3-pin 6A 1 India 2/3-pin 6A surge
Cable length	1.52 m
Number of cables	1
Battery type	Lead-acid battery

General

Provided equipment	user manual
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	28.2 cm
Width	13.2 cm
Depth	25.9 cm
Net weight	8.98 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	45...65 Hz auto-sensing
Plug standard	India 3-pin 6A
Input voltage limits	145...290 V
Switching current capacity	7 A

Output

Maximum configurable power in W	660 W
Output frequency	50 Hz sync to mains
UPS type	Line interactive
Waveform Type	Stepped approximation to a sinewave
Efficiency	72 % (full load) 84 % (half load)
Full load runtime	660 W
Maximum configurable power in VA	1100 VA
Transfer time	10 ms typical : 12 ms maximum

Conformance

Product certifications	BIS
------------------------	-----

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0...15000 m
Acoustic level	45 dBA

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	6 h
Number of battery replacement quantity	2
Battery voltage	24 V
Battery power in VAh	128 VAh runtime
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	255 J
-------------------	-------

Packing Units

Package 1 Weight	10.21 kg
------------------	----------

Package 1 Height	39.4 cm
------------------	---------

Package 1 width	20.3 cm
-----------------	---------

Package 1 Length	38.4 cm
------------------	---------

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
------------------	-----------------------------------

EU RoHS Directive	Compliant EU RoHS Declaration
-------------------	--

Mercury free	Yes
--------------	-----

RoHS exemption information	Yes
----------------------------	---------------------

Environmental Disclosure	Product Environmental Profile
--------------------------	---

Circularity Profile	End of Life Information
---------------------	---

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

Take-back	Take-back program available
-----------	-----------------------------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------
