

## Technical Spec

Type	ATX12V V2.4
Product Dimensions	150×140×86mm (W x L x H)
80PLUS Certifications	GOLD
Fan Size	120mm
Fan Bearing	Hypro Bearing
Topology	Active PFC + Full Bridge SRC LLC + DC to DC
Capacitors	Japanese Bulk Capacitor
Power Good Signal	100-150ms
Hold Up Time	≥16ms(75% Load)
Efficiency	≥90% Under Typical Load(50% Loading)
Protection	OPP/OVP/SCP/OTP/OCP/UVP
Operation Temperature	0-40°C
Regulatory	TUV/cTUVus/CCC/CE/FCC/UKCA/EAC/BIS
Erp Regulation	ErP(2014)
MTBF	100,000 Hours
EAN P/N	6933412701620 R-PM850D-FA0B-AU 6933412701637 R-PM850D-FA0B-CN 6933412701644 R-PM850D-FA0B-EU 6933412701651 R-PM850D-FA0B-JP 6933412701668 R-PM850D-FA0B-UK 6933412701675 R-PM850D-FA0B-US 6933412701682 R-PM850D-FA0B-WO 6933412711216 R-PM850D-FA0B-AR 6933412711223 R-PM850D-FA0B-BR 6933412711230 R-PM850D-FA0B-BU