

Technical Spec

Type	ATX12V V2.4
Product Dimensions	150×140×86mm (W x L x H)
80PLUS Certifications	GOLD
Fan Size	120mm
Fan Bearing	FDB
Topology	Active PFC + Full Bridge SRC LLC + DC to DC
Capacitors	Full Japan Electrolytic Capacitors
Power Good Signal	100-500ms
Hold Up Time	≥16ms (80% load))
Efficiency	≥90% Under Typical Load(50% Loading)
Protection	OPP/OVP/SCP/OTP/OCP/UVP
Operation Temperature	0 - 40 °C
Regulatory	CCC/CE/FCC/TUV-SUD/cTUVus/RCM/EAC/CAN ICES-003(B)/NMB-003(B)/UKCA
Erp Regulation	ErP 2013
MTBF	100,000 Hours
Warranty	10 Years
EAN P/N	6933412702009 R-PQA00M-FA0B-CN 6933412702016 R-PQA00M-FA0B-AU 6933412702023 R-PQA00M-FA0B-EU 6933412702030 R-PQA00M-FA0B-JP 6933412702047 R-PQA00M-FA0B-UK 6933412702054 R-PQA00M-FA0B-US 6933412702061 R-PQA00M-FA0B-AR 6933412702078 R-PQA00M-FA0B-BR 6933412702085 R-PQA00M-FA0B-WO 6933412702092 R-PQA00M-FA0B-BP