













FEATURES

SickleFlow 120 ARGB Fan - Redesigned curved blades and frame optimizes airflow and air pressure

Direct Contact Technology - Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation

Quiet Operation - Performance silent fan with minimized vibrations provides noiseless operation

Precise Combination of Air Flow and Heatsink - Stacked-fin array provides low airflow resistance allowing cooler air flow through the heatsink

Mini Addressable RGB LED Controller – Included Mini ARGB controller gives you versatility to showcase your favorite color arrays

Iconic Performance with ARGB Vibrance

The Hyper 212 ARGB delivers both optimal balance of airflow and performance with the vibrant lighting of addressable RGB. The new SickleFlow 120 fan boasts an upgrade fan blade and frame design to enhance cooling capabilities while maintaining silent operation. The heatsink utilizes 4 copper heat pipes and Cooler Master's Direct Contact Technology for extraordinary heat dissipation. The addressable RGB syncs with certified motherboards utilities, with an included Mini Addressable RGB controller to showcase your desired color spectrum.

SPECIFICATIONS

3PEGIFICATION3					
Product Name		Hyper 212 ARGB			
Product Nur	mber	RR-2V2L-18PA-R1			
Exterior Col	or	Silver & Black			
CPU	Intel	LGA 1200 / 1151 / 1150 /1155 / 1156			
Socket	AMD	AM4			
Heatsink	Dimensions (L x W x H)	120 x 80.5 x 157 mm (4.7 x 3.2 x 6.2 inch)			
	Material	Copper & Aluminum			
	Heat pipes	4			
	Dimensions (L x W x H)	120 x 120 x 25 mm (4.7 x 4.7 x 1 inch)			
	Quantity (pcs)	1 pc			
	LED Type	ARGB			
	Speed (RPM)	650 ~ 1800 RPM (PWM) ± 5%			
	Airflow (CFM)	62 CFM (Max)			
Fan	Noise Level (dBA)	8 ~ 27 dBA			
	Pressure (mmH2O)	2.5 mmH2O (Max)			
	MTTF	160,000 hours			
	Power Connector	4-Pin (PWM)			
	Rated Voltage (VDC)	12 VDC			
	Rated Current (A)	0.15A			
Warranty		2 years			

PACKING INFORMATION

EAN code	4719512110218	
UPC code	884102082528	
Net weight	0.61 kg	
Gross weight	0.76 kg	
Package dimension (L x W X H)	160 x 100 x 231 mm	
Carton dimension (L x W x H)	515 x 335 x 265 mm	
Units/CTN	10	

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20′	4800	42	N/A
40′	9600	42	N/A
40 HQ	10800	48	N/A

FEATURES & SYSTEM REQUIREMENTS



Mini Addressable RGB LED Controller

Included Mini ARGB controller gives you versatility to showcase your favorite color arrays.



SickleFlow ARGB Fan

Redesigned curved blades and frame optimizes airflow and static pressure



Direct Contact Technology

Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation



Easy installation

Improved universal bracket design simplifies installation process.