



Make It Yours.

HYPER WHITE 600
MPE-6001-ACAAH-H

POWER UP



FEATURES

Active PFC + Forward Topology Design : Constructed with protective measures normally found in high-end power supplies to increase safety and current stability.

80% Efficiency : The 80 PLUS White certification guarantees a minimum efficiency of 80%.

Durable, Reliable, and Safe : Will perform consistently in whatever environment whether it's high altitudes or ultra humid settings.

3 Year Warranty : This unit comes with a standard limited manufacturing warranty of 3 years from the date of purchase.

PACKAGE INFORMATION

Cable Type	EAN	UPC
US	4719512120156	884102092473
BR	4719512120163	884102092480
WO	4719512120170	884102092497

Nett Weight	1.35 kg / 2.976 lb
Gross Weight	1.78 kg / 3.924 lb
Package Dimensions	245 x 190 x 95mm (9.65 x 7.48 x 3.74")
Carton Dimensions	495 x 260 x 215mm (19.49 x 10.24 x 8.46")
Unit / Carton	5 pcs
Carton / Pallet	64 pcs

The Hyper White power supply unit is a dependable choice for entry level users and system integrators. The quiet 120mm fan, Active PFC, and 3 year warranty deliver a PSU that provides function and resilience you can count on. It's the perfect option for work horse systems stored and operated in less than ideal conditions and climates. This power supply unit has been engineered for reliability with a focus on reducing random shutdowns in conditions where power sources are inconsistent and unstable. Hyper White is a complete solution, offering performance and stability at an affordable price.

SPECIFICATIONS

Product Name	Hyper White 600	
Item Code	MPE-6001-ACAAH-H	
ATX Version	ATX 12V Ver. 2.41	
PFC	Active PFC	
Input Voltage	100 - 240V	
Input Current	10 - 5A	
Input Frequency	50 - 60Hz	
Dimensions (L x W x H)	140 x 150 x 86mm	
Fan Size	120mm	
Fan Bearing	Sleeve Bearing	
Efficiency	≥80% @ Typical Load	
80 PLUS Rating	80 PLUS White	
ErP 2014 Lot 3	Yes	
Operating Temperature	40°C	
Power Good Signal	100 - 500 ms	
Hold Up Time	≥ 10ms at 100% load	
MTBF	>100,000 hours	
Protections	OVP / OPP / OTP / SCP / UVP	
Regulatory	TUV / cTUVus / CE / BSMI / FCC / EAC / CCC / CB / S-MARK	
Connectors	ATX 24 Pin	x1
	EPS 4+4 Pin	x1
	SATA	x5
	Peripheral 4 Pin	x3
	PCI-e 6+2 Pin	x2

AC INPUT	100 - 240V~ 10 - 5A 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	20A	20A	46A	0.3A	3A
TOTAL POWER	120W		552W	3.6W	15W
	600W				

