




SPECIFICATIONS

Model Name	GeForce RTX® 4080 12GB SUPRIM
Graphics Processing Unit	NVIDIA® GeForce RTX® 4080 12GB
Interface	PCI Express® Gen 4
Core Clocks	Boost: TBD MHz
CUDA® CORES	7680 Units
Memory Speed	21 Gbps
Memory	12GB GDDR6X
Memory Bus	192-bit
Output	DisplayPort x 3 (v1.4a) HDMI™ x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	Y
Power consumption	TBD
Power connectors	16-pin x 1
Recommended PSU	700W
Card Dimension (mm)	338 x 142 x 73 mm
Weight (Card / Package)	TBD
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680x4320

CONNECTIONS



FEATURES

- TRI FROZR 3S**
 Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.
- Airflow Control**
 Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.
- TORX FAN 5.0**
 Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.
- Air Antegrade Fin**
 A section of V-shape heatsink and side-fins work to refocus air resistance at the passthrough.
- Copper Baseplate**
 Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.
- Core Pipe**
 Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.
- Metal Backplate**
 Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.
- MSI Center**
 The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.