

GRAPHICS CARDS GEForce RTX® 4080 16GB GAMING TRIO







SPECIFICATIONS

Model Name	GeForce RTX [®] 4080 16GB GAMING TRIO
Graphics Processing Unit	NVIDIA® GeForce RTX [®] 4080 16GB
Interface	PCI Express [®] Gen 4
Core Clocks	TBD
CUDA [®] CORES	9728 Units
Memory Speed	23 Gbps
Memory	16GB GDDR6X
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4a) HDMI [™] x 1 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	<u>Y</u>
Power consumption	TBD
Power connectors	16-pin x 1
Recommended PSU	750 W
Card Dimension (mm)	337 x 140 x 67 mm
Weight (Card / Package)	TBD
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC [®] technology	<u>Y</u>
Digital Maximum Resolution	7680x4320

CONNECTIONS



Display Port
HDMI

FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.

TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.

Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.

Core Pipe



Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.

Airflow Control



Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.

Anti Bending



A die-cast anti-bending plate reinforces the card while thermal pads allow cooling to reach critical component underneath.

Metal Backplate



Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.

Dual BIOS



Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.

