# **GeForce RTX® 4090 SUPRIM X 24G**







## **SPECIFICATIONS**

Model Name	GeForce RTX® 4090 SUPRIM X 24G
Graphics Processing Unit	NVIDIA® GeForce RTX® 4090
Interface	PCI Express <sup>®</sup> Gen 4
Core Clocks	TBD
CUDA® CORES	16384 Units
Memory Speed	21 Gbps
Memory	24GB GDDR6X
Memory Bus	384-bit
Output	DisplayPort x 3 (v1.4a) HDMI $^{\rm m}$ x 1 (Supports 4K @120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
HDCP Support	Y
Power consumption	TBD
Power connectors	16-pin x 1
Recommended PSU	850W
Card Dimension (mm)	336 x 142 x 78 mm
Weight (Card / Package)	2413g /3636g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Y
Digital Maximum Resolution	7680 x 4320

## CONNECTIONS



- 1. DisplayPort
- 2. HDMI

## **FEATURES**



### **TRI FROZR 3S**

Push performance with the latest MSI cooling design and elevate sophistication with a prestigious appearance.



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



### Vapor Chamber

The GPU and memory modules are covered with a Vapor Chamber which rapidly transfers heat to Core Pipes.



### **Core Pipe**

Precision-machined heat pipes ensure max contact and spread heat along the full length of the heatsink.



### **Airflow Control**

Don't sweat it, Airflow Control guides the air to exactly where it needs to be for maximum cooling.



## Zero Frozr

The fans completely stop when temperatures are relatively low, eliminating all noise.



# **Metal Backplate**

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.





Additional efficiency is gained by adjusting the size of the wave edges under the fan motor and other spots where there is less airflow.