DAHUA TECHNOLOGY

ASA1222E-S
Time & Attendance Terminal

Features

· TCP/IP based

· External electronic bell

. 2.4 inches TFT colorful screen

· Extremely speed verification

· Multiple verification methods (FP/PWD, only FP, only PWD)

· USB flash upgrade firmware

. Generate Smart Time Attendance reports in standalone

· 6 kinds of attendance events:
  Check In/Out, Break In/Out, Over Time In/Out

· Daylight saving time

· T9 text input

· two user roles: administrator and normal user

· Administrator operation record display

· All users allowed to query his attendance records

. Human voice operation prompts

Technical Specification

Model	ASA1222E-S

System

Main Processor	32 bit
Memory	16MB Flash

Interface

TCP/IP	Yes
USB	Host
Relay	1 Relay (Electronic Bell)

Fingerprint

Response Time	≤1.5s
FAR	≤0.00004%
FRR	≤0.15%

Capacity

Fingerprint	2,000
User	1,000
Attendance Records	100,000
Management Records	10,000

Function

User Level	Admin,User
Schedule Mode	by User/by Department
Verification Mode	Fingerprint/Password, Only Fingerprint, Only Password

General

Voice Prompt	Yes
Power Supply	DC 5V/1000mA
Operating Temperature	-10°C to +55°C
Working Humidity	5%–95%
Dimension(W×D×H)	175mm×120mm×23mm
Weight	0.35kg
Working Environment	Indoor

Certificates

CE	Yes
FCC	Yes

ASA1222E-S

Dimensions

Application