

**CP- UNC-DA41ZPL4-MD****4 MP WDR Network IR Dome Camera - 40Mtr.****Main Features**

- 1/3" 4MP PS CMOS Image Sensor
- Max. 4MP (2560 x 1440)@25/30fps, and Max. 4MP (2688 x 1520)@20fps
- H.265+ and H.264+ dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, ROI, AGC, BLC, HLC
- 2.8mm~12mm Motorized Lens
- IR Range of 40 Mtrs, Micro SD Card, IP67, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP-UNC-DA41ZPL4-MD

## 4 MP WDR Network IR Dome Camera - 40Mtr.

### Feature

Image Sensor  
 Minimum Illumination  
 Effective Pixels  
 Shutter Speed  
 White Balance  
 Lens  
 Gain Control (AGC)  
 Angle of View  
 Video Compression  
 Back Light Compensation  
 Video Streaming  
 Resolution  
 Motion detection  
 Privacy Mask  
 ICR  
 ROI  
 Bit Rate  
 Protocol  
 Abnormality Detection  
 Ethernet  
 User Account  
 Smart Phone  
 IR  
 Micro SD  
 Ingress Protection  
 Operating Temperature

### Specification

1/3" 4MP Progressive scan CMOS  
 0.03 Lux@F1.7  
 2688(H) x 1520(V)  
 Auto/Manual, 1/3~1/100000s  
 Auto/natural/street lamp/outdoor/manual/regional custom  
 2.8mm~12mm Motorized lens  
 Auto/Manual  
 Horizontal: 98°-31° Vertical: 55°-18° Diagonal: 116°-36°  
 H.265+/H.265/H.264+/H.264/H.264B/MJPEG  
 BLC / HLC / WDR(120dB)  
 Main Stream: 2688 x 1520 (1 fps-20 fps) 2560 x 1440 (1 fps-25/30 fps) Sub Stream: 704 x 576 (1 fps-20/25 fps) 704 x 480 (1 fps-20/30 fps)  
 2688 x 1520 (2688 x 1520); 2560 x 1440 (2560 x 1440); 2304 x 1296 (2304 x 1296); 1080P (1920 x 1080); 1.3MP (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480)  
 OFF/ON (4 areas, rectangular)  
 4 areas  
 Auto (ICR)/Color/B/W  
 Yes (4 areas)  
 H.264: 32 Kbps-6144 Kbps H.265: 12 Kbps-6144 Kbps  
 HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP; ONVIF (Profile S/Profile G); CGI; Milestone; Genetec; P2P  
 Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection  
 RJ-45 (10/100Base-T)  
 20 Users  
 iPhone, iPad, Android Phone  
 IR Range of 40 Mtr., Smart IR  
 Micro SD card (support max. 256GB); NAS; FTP  
 IP67  
 -30°C to +55°C (-22°F to +131°F) /less than≤95%

**CP- UNC-DA41ZPL4-MD****4 MP WDR Network IR Dome Camera - 40Mtr.****Feature**

Power Source

Power Consumption

Casing

Dimension

Weight

**Specification**

DC12V, PoE (802.3af)

&lt; 6.4W

Plastic

98.1 mm × Φ122 mm (3.9" × Φ4.8")

0.39 kg