

CP- UNC-DB21L3C-MDS**2MP Full HD WDR IR Network Dome Camera - 30Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor
- 25/30fps@1080P(1920x1080)
- Support Starlight Function
- H.265+ and H.264+ Dual-stream encoding
- WDR(120dB), Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 3.6mm fixed lens (2.8mm optional)
- IR Range of 30 Mtrs, IP67, Micro SD Card, PoE
- Support Built-in Mic
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNC-DB21L3C-MDS

2MP Full HD WDR IR Network Dome Camera - 30Mtr.

Feature

Image Sensor
Minimum Illumination
Effective Pixels
Shutter Speed
White Balance
S/N Ratio
Lens
Gain Control (AGC)
Video Compression
Angle of View
Back Light Compensation

Video Streaming

Resolution

Motion detection

Privacy Mask

ICR

ROI

Audio Compression

Audio

Bit Rate

Protocol

Smart Detection

Ethernet

Event Trigger

User Account

IR

Specification

1/2.8" 2MP Progressive scan CMOS
0.002 Lux @F1.6
1920(H) x 1080(V)
Auto/Manual 1/3 s-1/100000 s
Auto/natural/street lamp/outdoor/manual/regional custom
>56dB
3.6mm (2.8mm optional)
Auto/Manual
H.265+; H.265; H.264+; H.264; H.264B; MJPEG (only supported by the sub stream)
2.8mm: H: 106.0° V: 56.0° D: 126.0° , 3.6mm: H: 87.0° V: 46.0° D: 104.0°
BLC / HLC / WDR(120dB)
Main stream:1920 x 1080 (1 fps-25/30 fps)
Sub stream: 704 x 576 (1 fps-25 fps) 704 x 480 (1 fps-30 fps)
1080P (1920 x 1080); 1.3MP (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); VGA (640 x 480); CIF (352 x 288/352 x 240)
Disable/Enable (4 areas, rectangle)
4 areas
ICR switch
Yes (4 areas)
G.711A; G.711Mu; G.726; AAC
Built-in Mic
H.264: 32 Kbps-6144 Kbps, H.265: 12 Kbps-6144 Kbps
HTTP; TCP; ARP; RTSP; RTP; UDP; RTCP; SMTP; FTP; DHCP; DNS; DDNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; RTMP; Multicast; HTTPS; SFTP; 802.1x; ICMP; IGMP; ONVIF (Profile S/Profile G/Profile T); CGI; Milestone; Genetec
Tripwire, Intrusion
RJ-45 (10/100Base-T)
Abnormality detection: Motion detection, video tempering, no SD card, SD card full, SD card error, network disconnected, IP conflict, illegal access, voltage detection
20 Users
IR Range of 30 Mtr.

CP- UNC-DB21L3C-MDS

2MP Full HD WDR IR Network Dome Camera - 30Mtr.

Feature

Smart Phone

Micro SD Card

Storage Temperature

Operating Temperature

Humidity

Power Source

Power Consumption

Weatherproof Standard

Casing

Dimension

Weight

Specification

iPhone, iPad, Android Phone

FTP; Micro SD card (max. 256 GB); NAS

-40°C to +60°C (-40°F to +140°F)

-40°C~+60°C, Less than 95%RH

≤95%

DC12V, PoE

< 6.5W

IP67

Metal + Plastic

100.9 mm × Φ109.9 mm (3.97" × Φ4.33")

0.39kg