

**CP- UNC-TA21ZPL5-M****2MP Full HD IR Bullet Camera - 50Mtr.****Main Features**

- 1/2.8" 2MP PS CMOS Image Sensor (0.9071 cm)
- Max 25/30fps@2MP
- H.265+ and H.264+ dual-stream encoding
- DWDR, Day/Night (ICR), 3D-DNR, ROI, AWB, AGC, BLC, HLC
- 2.8mm~12mm Motorized Lens
- IR Range of 50 Mtrs, IP67, Micro SD Card, PoE
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



# CP- UNC-TA21ZPL5-M

## 2MP Full HD IR Bullet Camera - 50Mtr.

### Feature

Image Sensor

Minimum Illumination

Effective Pixels

Shutter Speed

S/N Ratio

White Balance

Lens

Gain Control (AGC)

Video Compression

Back Light Compensation

Angle of View

DORI Distance

Resolution

Frame Rate

Motion detection

Privacy Mask

ICR

ROI

OTA (Online Device Upgrade)

Bit Rate

Protocol

Abnormality detection

Alarm Event

Cyber Security

### Specification

1/2.8" 2Megapixel progressive CMOS (0.9071 cm)

0.005 Lux@F1.5

1920(H)x1080(V)

Auto/Manual, 1/3~1/100000s

>56dB

Auto/natural/street lamp/outdoor/manual/regional custom

2.8mm~12mm Motorized lens

Auto/Manual

H.265+/H.265/H.264+/H.264H/H.264B/ MJPEG (only supported by Sub stream)

BLC / HLC / DWDR

Pan: 101°-33.5° Tilt: 52.5°-19° Diagonal: 125°-38.5°

W: 48m (Detect) 19m (Observe) 10m (Recognize) 5m (Identify)

T: 131m (Detect) 52m (Observe) 26m (Recognize) 13m (Identify)

1080P (1920 × 1080); 1.3MP (1280 × 960); 720P (1280 × 720); D1 (704 × 576/704 × 480);  
VGA (640 × 480); CIF (352 × 288/352 × 240)

Main Stream: 1920 × 1080 (1 fps-25/30 fps) Sub stream: 704 × 576 (1 fps-25 fps)  
704 × 480 (1 fps-30 fps)

OFF/ON (4 areas, rectangular)

4 areas

Auto (ICR)/Color/B/W

Yes (4 areas)

Support

H.264: 32 Kbps-6144 Kbps H.265: 12 Kbps-6400 Kbps

IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; NTP; Multicast; ONVIF  
(Profile S/Profile T); CGI; InstaOn; Genetec; milestone

Motion detection, video tampering, network disconnection, IP conflict, illegal access

No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; mo-  
tion detection; video tampering; safety abnormality; defocus detection

Video encryption; configuration encryption; Digest; WSSE; account lockout; security logs;  
generation and importing of X.509 certification; HTTPS; trusted boot; trusted execution;  
trusted upgrade

# CP- UNC-TA21ZPL5-M

2MP Full HD IR Bullet Camera - 50Mtr.

## Feature

SDK and API

Ethernet

User/ Host

Smart Phone

IR

Micro SD

Operating Temperature

Power Source

Power Consumption

Weatherproof Standard

Casing

Dimension

Weight

## Specification

Yes

RJ-45 (10/100Base-T)

6 Users

iPhone, iPad, Android Phone

IR Range of 50 Mtr., Smart IR

FTP; Micro SD card (support max. 256 GB)

-30°C to +60°C (-22°F to +140°F) /less than ≤ 95% RH

DC12V, PoE (802.3af)

1.4W (12V DC); 2.2W (PoE)

IP67

Metal + plastic

243.5 mm × Φ90.7 mm (9.6" × Φ3.6")

0.43 kg