



### DIGISOL 24 Port Gigabit Ethernet Layer 2 Web managed Switch with 4 Gigabit SFP Ports

**DG-GS1528** 

#### **Key Features:-**

- 24 X 10/100/1000Base-Tx + Gigabit 4 SFP Ports
- STP / RSTP / MSTP
- · Loop detection
- IGMP Snooping
- SNMP
- · Quality of Service (QoS)



#### Introduction:-

**DIGISOL** DG-GS1528 is a Lite-Managed switching product. It is a intelligent network manageable switch designed for network environments that require high performance, high port density and easy for installation. It provides 24 Gigabit Ethernet and 4 SFP Giga. It supports VLAN, Port Mirroring and Port Trunking.

#### Performance and Scalability

It's a great entry level managed switch with 56 Gbps switching capacity. Wire-speed switching performance helps to take full advantage of existing high-performance on PCs and laptops by significantly improving the responsiveness of applications and file transfer times. The device also has Four Gigabit SFP ports for high speed uplinks to servers or backbones.

#### Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loopfree network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability. IEEE802.3ad Link Aggregation Control Protocol (LACP) increases bandwidth by automatically aggregating several physical links together as a logical trunk and providing load balancing and fault tolerance for uplink connections.

#### Comprehensive QoS

 $Traffic is prioritized \, according \, to \, 802.1 p \, giving \, optimal \, performance \, to \, real \, time \, applications \, such \, as \, voice \, and \, video.$ 

#### **Enhanced Security**

Port Security ensures access to switch ports based on MAC address. Thus limiting the total number of devices from using a switch port and protects against MAC flooding attacks.

#### Simplified Management

 $User friendly web interface facilitates \ ease of management. \ It \ also \ supports \ to \ be \ managed \ and \ controlled \ by \ network station.$ 



# DIGISOL.

## **SWITCHING SOLUTIONS**



Manufacturing Since 1986

#### **Technical Specifications:-**

#### **Physical Port**

- 24 10/100/1000 Base-T Ethernet Ports
- · 4 Gigabit SFP Ports

#### **Performance**

- Switching Capability: 56Gbps
- MAC Address Table: 8K
- · Memory Per Unit: 2.4MB
- · Jumbo Frame: 10K

#### L2 Features

- Auto-negotiation for port speed and duplex mode
- Spanning Tree Protocol
  - Support STP / RSTP / MSTP (max 16 instance)
  - Loopback Detection
  - BPDU Filter
  - BPDU Guard
- IGMP v1/v2/v3 Snooping: IGMP Querier IGMP Proxy MVR
- VLANs
  - 256 IEEE 802.1q tag based VLAN with 4K vlan ID
  - Port Isolation (Multi-to-one)
  - Port Based VLAN
  - MAC Based VLAN
  - Voice VLAN
  - Guest VLAN

- · Link Aggregation
  - LACP: 8 Groups, 8 Ports/Group
  - Static Trunk

#### **QoS Features**

- · Queueing Mechanism: SP and WRR
- · Classifications based on
  - COS
  - COS DSCP
  - IP Precendence
- · Each port supports 8 queues
- · Rate Limit (Port Based)
- · Flow Control

- · Mac address Binding
- Support Broadcast storm control
- IP and MAC ACL
- · RADIUS, AAA
- · Port Security, Protected Port
- · DHCP Snooping, IP Source Guard

#### Management

- · Port Mirroring
- Support traffic statistics
- Provide IPv4 Web-based management
- · Configuration Backup and Recovery
- Management VLAN
- SNMP v1/v2c/v3
- · Telnet, SSH, HHTPS

#### RMON, SNTP

- · Ping, Traceroute
- · Dual Firmware Image
- UDLD, EEE

#### **Power Supply**

- AC Power: 100 to 240 V, 50-60 Hz
- Input Surge Protector

#### **Standards**

- IFFF 802 3 10BASE-T
- IEEE 802.3u 100BASE-TX
- IEEE 802.3ab 1000BASE-T
- IEEE 802.3z, IEEE 802.3x
- ANSI/IEEE 802.3 Nway

#### **Environmental Specifications**

- Temperature: 0°C~40°C (Standard Operating) 40°C to 70°C (Non-Operating)
- Humidity: 10% to 90% (Non-condensing)

#### Mechanical

- Dimensions (WxDxH): 441mm x 198mm x 44mm
- · LED Indicators: Power, Link/Act
- · Hardware Factory Reset button

#### **Optional Accessories:-**

DG-SA1030: DIGISOL 1000Base-SX SFP Transceiver LC Type DG-SA1133-20: DIGISOL 1000Base-LX SFP Transceiver LC Type







### **Ordering Information:-**

#### DG-GS1528: DIGISOL 24 10/100/1000Mbps Web Managed **Switch with 4 Gigabit SFP Ports**

\*Warranty shall be subject to terms and conditions specified in the DIGISOL PRODUCT WARRANTY displayed on the website of the company.

DIGISOL Logos are trademarks and/or registered trademarks of DIGISOL SYSTEMS LIMITED. Other trademarks, product, service and company names mentioned are the property of their respective owners. Information is subject to change without notice. The actual product appearance may differ from the one shown here. © 2021 DIGISOL SYSTEMS LIMITED. All rights reserved.





#### DIGISOL SYSTEMS LIMITED

215 Atrium Bldg., 305, A-Wing, 3rd Floor, Opp. Big Cinema, Courtyard Marriott Compound, Andheri-Kurla Road, Andheri (E), Mumbai - 400093.







1800-209-3444 🌘 www.digisol.com 🔯 helpdesk@digisol.com

¶@DIGISOLINDIA