




The Hyper H410R RGB, a new member of the longstanding Hyper Series, is an affordable, compact and high performance air cooler that its compact heatsink is a great match for small form factor system. The special fin design optimizes air flow toward heat pipes. Its 92mm squared RGB fan features a wide fan speed range and can be fine tuned for maximum airflow and cooling performance or silent operation. Compatible with all RGB certified motherboards.



HYPER H410R RGB



Direct Contact Technology

Direct Contact Technology using 4 copper heat pipes delivers exceptional heat dissipation



Precise Combination of Air Flow and Heatsink

Stacked fin array ensures minimum airflow resistance allowing cooler air into the heatsink.



Outstanding Performance in a Compact Size

Compact tower cooler, designed to fit in tight builds with height of 136.5mm



RGB LED Controller

The wired RGB LED Controller allows for customizable colors and effects with just the touch of a button

Outstanding Performance in a Compact Size - Compact tower cooler, designed to fit in tight builds with height of 136.5mm

Direct Contact Technology - 4 heat pipes with Direct Contact Technology effectively provide excellent heat dissipation.

Precise Combination of Air Flow and Heatsink -Stacked fin array ensures minimum airflow resistance allowing cooler air into the heatsink.

RGB LED Controller - The wired RGB LED Controller allows for customizable colors and effects with just the touch of a button

SPECIFICATIONS

Product Name	Hyper H410R RGB	
Product Number	RR-H410-20PC-R1	
Exterior Color	Silver	
CPU Socket	Intel® LGA 1700 / 1200 / 1151 / 1150 / 1155 / 1156 socket	
	AMD® AM5 / AM4 socket	
Dimensions (Lx W x H)	102 x 84.5 x 136 mm (4.0 x 3.3 x 5.3 inch)	
Heat Sink Material	4 Heat Pipes / Direct Contact / Aluminum Fins	
Fan		92mm Fan
	Dimensions (L x W x H)	92 x 92 x 25mm (3.6 x 3.6 x 1 inch)
	Profile	RGB
	Quantity (pcs)	1 PC
	Speed	600 ~ 2000 RPM ± 10%
	Airflow (Max)	59 m ³ /h (34.73 CFM)
	Pressure (Max)	1.86 mmH ₂ O
	MTTF	>40,000 Hours
	Noise Level (Max)	29.38 dB(A)
	Bearing	Rifle
	Power Connector	4-Pin PWM
	Rated Voltage	12 VDC
	Rated Current	0.19 A
	Safety Current	0.4 A
	Power Consumption	2..28 W
Warranty	2 years	

PACKING INFORMATION

EAN code	4719512094679
UPC code	884102067099
Net weight	0.5 kg
Gross weight	0.62 kg
Package dimension (L x W X H)	12 x 9.8 x 18.7 cm
Carton dimension (L x W x H)	60 x 38 x 22 cm
Units/CTN	18

Cont.	W/ Pallet	Carton/ Pallet	W/O Pallet
20'	7128	36	N/A
40'	14256	36	N/A
40 HQ	15840	40	N/A