

ViewSonic® LCD DISPLAY VA2209-H


Key Features

- SuperClear® IPS panel
- Full HD 1080p resolution
- 3-side borderless bezel
- Eyecare technology for comfortable viewing
- Adaptive sync to eliminate screen tearing and reduce stuttering



Product Description

The ViewSonic VA2209-H is a 22" Full HD monitor featuring HDMI and VGA inputs for business and home use. The optimal screen performance and comfortable viewing without tearing or stuttering is delivered through adaptive sync, eye-care technology, and various ViewMode presets. Simply expand your workspace and experience truly seamless, ergonomic multitasking on just one screen with a VESA-compatible mount at low power consumption.



1. HDMI
2. VGA
3. Audio Out
4. Power In
5. VESA Compatible(Wall Mount 100 x 100mm)

Visit Us www.viewsonic.com

DISPLAY

Display Size (in.):	22
Viewable Area (in.):	21.5
Panel Type:	IPS Technology
Resolution:	1920 x 1080
Resolution Type:	FHD (Full HD)
Static Contrast Ratio:	1,000:1 (typ)
Dynamic Contrast Ratio:	50M:1
Light Source:	LED
Brightness:	250 cd/m ² (typ)
Colors:	16.7M
Color Space Support:	8 bit (6 bit + FRC)
Aspect Ratio:	16:9
Response Time (Typical GTG):	4ms
Viewing Angles:	178° horizontal, 178° vertical
Backlight Life (Hours):	30000 Hrs (Min)
Curvature:	Flat
Refresh Rate (Hz):	75
Variable Refresh Rate Technology:	Yes
Blue Light Filter:	Yes
Flicker-Free:	Yes
Color Gamut:	NTSC: 72% size (Typ) sRGB: 104% size (Typ)
Pixel Size:	0.249 mm (H) x 0.241 mm (V)
Surface Treatment:	Anti-Glare, Hard Coating (3H)

COMPATIBILITY

PC Resolution (max):	1920x1080
Mac® Resolution (max):	1920x1080
PC Operating System:	Windows 10/11 certified; macOS tested
Mac® Resolution (min):	1920x1080

CONNECTOR

VGA:	1
3.5mm Audio Out:	1
HDMI 1.4:	1
Power in:	DC Socket (Center Positive)

POWER

Eco Mode (Conserve):	16W
Eco Mode (optimized):	18W
Consumption (typical):	20W
Consumption (max):	22W
Voltage:	AC 100-240V
Stand-by:	0.3W
Power Supply:	External Power Adaptor

ADDITIONAL HARDWARE

Kensington Lock Slot:	1
-----------------------	---

CONTROLS

Physical Controls:	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu

OPERATING CONDITIONS

Temperature:	32°F to 104°F (0°C to 40°C)
Humidity (non-condensing):	20% to 90%

WALL MOUNT

VESA Compatible:	100 x 100 mm
------------------	--------------

INPUT SIGNAL

Frequency Horizontal:	24 ~ 86KHz
Frequency Vertical:	50 ~ 75Hz

VIDEO INPUT

Digital Sync:	TMDS - HDMI (v1.4)
Analog Sync:	Separate - RGB Analog

ERGONOMICS

Tilt (Forward/Back):	-3° / 20°
----------------------	-----------

WEIGHT (IMPERIAL)

Net (lbs):	5.1
Net Without Stand (lbs):	4.2
Gross (lbs):	7.3

WEIGHT (METRIC)

Net (kg):	2.3
Net Without Stand (kg):	1.9
Gross (kg):	3.3

DIMENSIONS (IMPERIAL) (WXHXD)

Packaging (in.):	21.5 x 15.6 x 4.7
Physical (in.):	19.3 x 15 x 7.4
Physical Without Stand (in.):	19.3 x 11.5 x 1.6

DIMENSIONS (METRIC) (WXHXD)

Packaging (mm):	545 x 395 x 120
Physical (mm):	491 x 381 x 189
Physical Without Stand (mm):	491 x 291 x 39

GENERAL

Regulations:	RoHS, WEEE, BSMI, TGM, BIS
PACKAGE CONTENTS:	VA2209-H x1, HDMI Cable (v1.4: Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
Warranty:	*Warranty offered may differ from market to market